ा राष्ट्रदेवो भवः ा



V5 Borewell Pumps

Agriculture V5 GH, GRS & FMQ Series Borewell Submersible Pumpsets



Specially Designed for High Head Series

First Time in India, BEE 5 Star Ratings Pumps in 50+ Models in V6 Borewell Series (As per Latest BEE Guideline 2020)

V-6/V-5

GRS Janta

V-5

GH

V-5

GRS / GRSS

V-5

FMQ



Chale Pragati Ki Aur®



AGRICULTURE BOREWELL PUMPS

HP Range	: 3.0 HP to 12.5 HP
Head Range	: 10 Mtr. to 640 Mtr.
Discharge Range	: 740 LPM to 40 LPM

V5 BOWLSET PERFORMANCE DATA

Bowl Range	Installation Head Range in Mtr, (Uniform Output)	Discharge in Head LPM to LPM	Material Bowl & Impeller
GH Series	4 - 8	240 - 40	Engineering Glass Filled Virgin Plastic Bowlset with 4 NOS. SS Neckring
GRS Series	6 - 10	210 - 40	SS-304 Grade Investment Casting Bowl with Nylon 66 Impeller
GRSS Series	6 - 10	210 - 40	SS-304 Grade Investment Casting Bowl with SS-304 Grade Sheet Metal Impeller
FMQ Series	4 - 7	690 - 180	CED Coated CI Bowl with SS-410 Impeller

✓ Available in Single Phase: 3.0 HP to 5.0 HP, Voltage Range: 180V to 240V 50Hz., 2880 RPM

- ✓ Available in Single Phase (Janta Model): 3.0HP to 10 HP (V6 Premium Motor) Voltage Range: 180V to 240V 50Hz. 2880 RPM
- ✓ Available in Three Phase: 3.0HP to 12.5HP Voltage Range: 350V to 415V 50HZ., 2880 RPM
- Available in Three Phase (Janta Model): 15 HP to 25HP (V6 Premium Motor) Voltage Range: 350V to 415V 50Hz.
 2880 RPM
- ✓ Specially designed for High Head Series V-6 Premium Motor with V-5 GRS/GRSS Pump (Janta Model) up to 25 HP Range
- ✓ Available in **Fully SS Pump Set** (Janta Model) GRS/GRSS Series.
- Outlet Size in Inch: 1.25", 1.5" & 2.0"

Z 0

υ

C I F I

ш

Ω.

ທ

